

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Product name : Tile Power
 Product code : 20
 Product group : Blend

1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Tile, chrome, and bathroom cleaner.
 Recommended use : Washing and cleaning products (including solvent based products)

1.3. Supplier

Nypower Industries Ltd.
 111 Fisher St.
 P.O. Box PO Box 715
 Okotoks, AB - Canada
 T 403 995-2598 - F 403 995-1487
gm@nypowerind.com - www.nypowerind.com

1.4. Emergency telephone number

Emergency number : 403 899-4226

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flammable liquids Category 3 H226 Flammable liquid and vapor
 Skin corrosion/irritation Category 1 H314 Causes severe skin burns and eye damage
 Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage
 Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA labeling

Hazard pictograms (GHS CA) : 

Signal word (GHS CA) : Danger

Hazard statements (GHS CA) : H226 - Flammable liquid and vapor
 H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 - Keep container tightly closed.
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 - Wash hands thoroughly after handling.
 P280 - Wear eye protection, protective gloves.
 P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 - Immediately call a doctor, a POISON CENTER.
 P363 - Wash contaminated clothing before reuse.
 P370+P378 - In case of fire: Use dry extinguishing powder, carbon dioxide (CO2), foam to extinguish.
 P403+P235 - Store in a well-ventilated place. Keep cool
 P405 - Store locked up.
 P501 - Dispose of contents/container to Collection point.

2.3. Other hazards

No additional information available

Tile Power

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2.4. Unknown acute toxicity (GHS CA)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Glycol Ether EB		(CAS-No.) 111-76-2	1 – 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
First-aid measures general	: Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Flammable vapors may accumulate in the container. Flammable liquid and vapor.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

Tile Power

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Flammable vapors may accumulate in the container. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.
- Hygiene measures : Always wash hands after handling the product. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Green
- Odor : No data available
- Odor threshold : No data available
- pH : 1.12
- pH solution : 1.12
- Relative evaporation rate (butyl acetate=1) : No data available
- Relative evaporation rate (ether=1) : No data available
- Melting point : -2 °C
- Freezing point : -2 °C
- Boiling point : 101 °C
- Flash point : 44 °C
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : Not applicable
- Vapor pressure : No data available
- Vapor pressure at 50 °C : No data available
- Relative density : No data available
- Specific gravity / density : 1.127 kg/l
- Solubility : Water: 100 %
- Partition coefficient n-octanol/water (Log Pow) : No data available

Tile Power

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Explosion limits	: No data available
Flammability limit - upper	: Not applicable
Flammability limit - lower	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: Flammable vapors may accumulate in the container. Flammable liquid and vapor.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Glycol Ether EB (111-76-2)	
ATE CA (oral)	500 mg/kg body weight
ATE CA (Dermal)	1100 mg/kg body weight
ATE CA (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes severe skin burns. pH: 1.12
Serious eye damage/irritation	: Causes serious eye damage. pH: 1.12
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Before neutralisation, the product may represent a danger to aquatic organisms.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

No additional information available

Tile Power

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1219
Packing group : II - Medium Danger
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids
Transport document description : UN1219 ISOPROPYL ALCOHOL, 3, II
Proper Shipping Name (Transportation of Dangerous Goods) : ISOPROPYL ALCOHOL

Hazard labels (TDG) : 3 - Flammable liquids



Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L

14.2. Transport information/DOT

Department of Transport

Not regulated for transport

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1219
Proper Shipping Name (IMDG) : ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport document description (IMDG) : UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II (12°C c.c.)
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger

IATA

Not regulated for transport

SECTION 15: Regulatory information

15.1. National regulations

Glycol Ether EB (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

Tile Power

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Glycol Ether EB (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

SDS Major/Minor : None
Issue date : 06/07/2021
Revision date : 07/19/2021
Supersedes : 07/19/2021

Full text of H-phrases:

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled

SDS Canada (GHS)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.